



### J720 Dental Printer

Speed. Productivity. Realism.



## Speed. Productivity. Realism.

The Stratasys J720™ dental 3D printer is designed to meet the increased demands labs face today. This full-color, multi-material printer produces high-resolution models with precise accuracy. It offers an unrivaled combination of speed, high throughput and realism to handle all dental case needs with the capacity to outperform DLP and SLA dental printers.

# Harness the Power of Color

- Increase patient acceptance of case presentations - show your patients how their treatment will look before starting work
- Leverage full-color capability to differentiate your lab, improve workflow and tracking, and communicate more information
- Reduce C&B remakes with the only dental printer able to create highly realistic replicas of the patient's mouth

#### Be More Productive



1.75X the throughput of leading competing DLP printers



Reduce material changeovers and eliminate the need for multiple printers by printing with six materials at once



Eliminate workflow planning by supporting all order needs in a single print job – IDB trays, aligner arches, C&B and implant cases



Large print capacity accommodates many cases at a time, reducing touch-time to load and process smaller printers with lower capacity







	Dental materials - VeroDent (MED670) and VeroDentPlus (MED690)
Model Materials	<ul> <li>Vero<sup>™</sup> family of opaque materials including neutral shades</li> </ul>
	<ul> <li>Vibrant colors including VeroCyanV<sup>™</sup>, VeroMagentaV<sup>™</sup> and VeroYellowV<sup>™</sup></li> </ul>
	<ul> <li>Tango™ and Agilus30™ families of flexible materials</li> </ul>
	<ul> <li>Transparent VeroClear™</li> </ul>
Digital Model Materials	Unlimited number of composite materials including:
	• Over 500,000 colors
	<ul> <li>Materials to replicate soft tissue in a variety of Shore A values</li> </ul>
	Translucent color tints
	User-developed digital materials
Support Materials	SUP705™ (WaterJet removable)
	SUP706B™ (soluble)
Build Size	490 x 390 x 200 mm (19.3 x 15.35 x 7.9 in.)
Layer Thickness	Horizontal build layers down to 14 microns (0.00055 in.)
Workstation Compatibility	Windows 7
Network Connectivity	LAN - TCP/IP
System Size and Weight	4 400 4 000 4 400 (55 4 40 0 40 4 1 ) 400 1 (0 40 11 )
System Size and Weight	1,400 x 1,260 x 1,100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.)
System Size and Weight	1,400 x 1,260 x 1,100 mm (55.1 x 49.6 x 43.4 in.); 430 kg (948 lbs.)  Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)
System Size and Weight  Operating Conditions	
Operating Conditions	<b>Material Cabinet:</b> 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)
	<b>Material Cabinet:</b> 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)  Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)
Operating Conditions	Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)  Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)  100–120 VAC, 50–60 Hz, 13.5 A, 1 phase
Operating Conditions  Power Requirements	Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)  Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)  100–120 VAC, 50–60 Hz, 13.5 A, 1 phase  220–240 VAC, 50–60 Hz, 7 A, 1 phase
Operating Conditions  Power Requirements  Regulatory Compliance	Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)  Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)  100–120 VAC, 50–60 Hz, 13.5 A, 1 phase  220–240 VAC, 50–60 Hz, 7 A, 1 phase  CE, FCC, EAC
Operating Conditions  Power Requirements  Regulatory Compliance	Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)  Temperature 18 − 25 °C (64 − 77 °F); relative humidity 30-70% (non-condensing)  100−120 VAC, 50−60 Hz, 13.5 A, 1 phase  220−240 VAC, 50−60 Hz, 7 A, 1 phase  CE, FCC, EAC  GrabCAD Print™
Operating Conditions  Power Requirements  Regulatory Compliance  Software	Material Cabinet: 670 x 1,170 x 640 mm (26.4 x 46.1 x 25.2 in.); 152 kg (335 lbs.)         Temperature 18 – 25 °C (64 – 77 °F); relative humidity 30-70% (non-condensing)         100–120 VAC, 50–60 Hz, 13.5 A, 1 phase         220–240 VAC, 50–60 Hz, 7 A, 1 phase         CE, FCC, EAC         GrabCAD Print™         High Speed: up to 3 base resins, 27-micron (0.001 in.) resolution



### Work Faster

- Faster time-to-part reduce the number of printers needed to maintain throughput and the labor required to monitor and service multiple printers
- Streamlined workflow print in different materials on the same build tray, maximizing productivity and accelerating throughput
- Quicker turnaround time for the same capacity, models are finished faster than competing systems
- Achieve speed and quality the J720 combines high-resolution printing with fast time-to-part

#### **Stratasys Headquarters**

7665 Commerce Way, Eden Prairie, MN 55344

- +1 800 801 6491 (US Toll Free)
- +1 952 937-3000 (Intl)
- +1 952 937-0070 (Fax)

stratasys.com ISO 9001:2008 Certified 1 Holtzman St., Science Park, PO Box 2496 Rehovot 76124, Israel +972 74 745 4000 +972 74 745 5000 (Fax)

